



2024 TOYOTA PROACE MAX Specifications

DIESEL POWERTRAIN	2.2 L 120HP	2.2 L 140HP	2.2 L 180HP
ENGINE TYPE	4 cylinders in-line	4 cylinders in-line	4 cylinders in-line
DISPLACEMENT (CM³)	2184	2184	2184
BORE X STROKE (MM)	83,8 x 99	83,8 x 99	83,8 x 99
COMPRESSION RATIO (:1)	15.5:1	15.5:1	15.5:1
MAX TORQUE (NM @ RPM)	320 @ 1400-2500	350 / 1400-2500	380 / 1500-3000
MAX TORQUE (NM @ RPM) with AT 8-SPEED	N.A.	380 / 1400-2250	450 / 1500-1750
MAX ENGINE POWER (DIN HP)	120	140	180
MAX ENGINE POWER (KW @ RPM)	88 @ 3500	103 @ 3500	132 @ 3500
EMISSION STANDARD	Euro 6	Euro 6	Euro 6
FUEL TANK CAPACITY (L)	90	90	90
TRANSMISSION TYPE	MT 6-SPEED	AT 8-SPEED or MT 6-SPEED	AT 8-SPEED or MT 6-SPEED

BATTERY ELECTRIC POWERTRAIN	BEV 110kWh		
BATTERY TYPE	LITHIUM-ION NMC PRISMATIC		
BATTERY CAPACITY (kWh)	110 kWh		
BATTERY WEIGHT (Kg)	650		
EV RANGE (KM)	420		
MAX OUTPUT (DIN HP / KW)	200 KW / 270 HP		
MAX. TORQUE (NM)	ECO	NORMAL	POWER
	360	380	410
ON-BOARD CHARGER	AC CHARGE		DC FAST CHARGE
	11 kW / 22 kW in 2025		150 kW
TRANSMISSION TYPE	AT		

PERFORMANCE PANEL VAN				
POWERTRAIN	2.2 L 120HP	2.2 L 140HP	2.2 L 180HP	BEV 110kWh
MAX. SPEED (KM/H)	148	156	170	130
ENERGY CONSUMPTION (L/100KM)				
MIN	7.6	7.5	8.1	N. A
MAX	8.8	9.9	10.4	N. A
				N. A
CO ₂ EMISSIONS (G/KM)				
MIN	200	198	213	N. A
MAX	233	262	275	N. A
				N. A

CHASSIS	
SUSPENSIONS (FRONT)	Independent, MacPherson type with wishbones, coil springs, telescopic shock absorbers and anti-roll bar
SUSPENSIONS (REAR)	Rigid tubular axle with parabolic longitudinal leaf springs, telescopic shock absorbers and flexible side buffers

EXTERIOR & LOAD DIMENSION (MM)	L2			L3			L4		
PANEL VAN									
GVW 3300									
	H1	H2	H3	H1	H2	H3	H1	H2	H3
OVERALL LENGTH	5413	5413	-	-	5998	-	-	-	-
OVERALL WIDTH (EXCL. / INCL. DOOR MIRRORS)	2050	2050	-	-	2050	-	-	-	-
OVERALL HEIGHT (STANDARD / INCREASED PAYLOAD)	2254	2524	-	-	2524	-	-	-	-
WHEELBASE	3450	3450	-	-	4035	-	-	-	-
CARGO AREA LENGTH (MM)	3120	3120			3705				
LOAD AREA VOLUME (M3)	10	11.5			13				
GVW 3500 LIGHT									
OVERALL LENGTH	5413	5413	-	-	5998	5998	-	-	-
OVERALL WIDTH (EXCL. / INCL. DOOR MIRRORS)	2050	2050	-	-	2050	2050	-	-	-
OVERALL HEIGHT (STANDARD / INCREASED PAYLOAD)	2254	2524	-	-	2524	2764	-	-	-
WHEELBASE	3450	3450	-	-	4035	4035	-	-	-
CARGO AREA LENGTH (MM)	3120	3120	-	-	3705	3705	-	-	-
LOAD AREA VOLUME (M3)	10	11.5	-	-	13	15	-	-	-
GVW 3500 HEAVY									
OVERALL LENGTH	-	5413	-	-	5998	5998	-	6363	6363
OVERALL WIDTH (EXCL. / INCL. DOOR MIRRORS)	-	2050	-	-	2050	2050	-	2050	2050
OVERALL HEIGHT (STANDARD / INCREASED PAYLOAD)	-	2539	-	-	2534/2612	2774/2850	-	2534/2612	2774/2850
WHEELBASE	-	3450	-	-	4035	4035	-	4035	4035
CARGO AREA LENGTH (MM)	-	3120	-	-	3705	3705	-	4070	4070
LOAD AREA VOLUME (M3)	-	11.5	-	-	13	15	-	15	17
GVW 4250 HEAVY									
OVERALL LENGTH	-	-	-	-	5998	5998	-	6363	6363
OVERALL WIDTH (EXCL. / INCL. DOOR MIRRORS)	-	-	-	-	2050	2050	-	2050	2050
OVERALL HEIGHT (STANDARD / INCREASED PAYLOAD)	-	-	-	-	2612	2850	-	2612	2850
WHEELBASE	-	-	-	-	4035	4035	-	4035	4035
CARGO AREA LENGTH (MM)	-	-	-	-	3705	3705	-	4070	4070
LOAD AREA VOLUME (M3)	-	-	-	-	13	15	-	15	17

EXTERIOR & LOAD DIMENSION (MM)	L2	L3	L4
PANEL VAN CREW CAB	H2		
GVW 3500 AND 4150 HEAVY			
OVERALL LENGTH	5413	5998	6363
OVERALL WIDTH (EXCL. / INCL. DOOR MIRRORS)	2050	2050	2050
OVERALL HEIGHT (STANDARD / INCREASED PAYLOAD)	2524	2534	2534/2612
WHEELBASE	3450	4035	4035
CARGO AREA LENGTH (MM)	1790	2375	2740
LOAD AREA VOLUME (M3)	9	10.5	12.5

EXTERIOR & LOAD DIMENSION (MM)	L3	L4
CHASSIS CAB & CHASSIS CREWCAB	H1	
GVW 3500 HEAVY AND 4250		
OVERALL LENGTH	5943	6308
OVERALL WIDTH	2050	2050
OVERALL HEIGHT	2254	2254
WHEELBASE	4035	4035
CARGO AREA LENGTH (MM)	N.A.	N.A.
LOAD AREA VOLUME (M3)	N.A.	N.A.

EXTERIOR & LOAD DIMENSION (MM)	L3	L4
DROPSIDE & DROPSIDE CREWCAB	H1	
GVW 3500 HEAVY AND 4250		
OVERALL LENGTH	6328/6228	6693/6678
OVERALL WIDTH	2100	2100
OVERALL HEIGHT	2424	2424
WHEELBASE	4035	4035
CARGO AREA LENGTH (MM)	3833/2888	4198/3338
LOAD AREA VOLUME (M3)	N.A.	N.A.

EXTERIOR & LOAD DIMENSION (MM)	L3	L4
PLATFORM CAB	H1	
GVW 3500 HEAVY		
OVERALL LENGTH	5943	6308
OVERALL WIDTH	2050	2050
OVERALL HEIGHT	2153	2153
WHEELBASE	4035	4035
CARGO AREA LENGTH (MM)	N.A.	N.A.
LOAD AREA VOLUME (M3)	N.A.	N.A.

EXTERIOR & LOAD DIMENSION (MM)	L3		
	H1		
GVW 3500 HEAVY AND 4250			
	TIPPER 1	TIPPER 3 WAY	TIPPER CREWCAB
OVERALL LENGTH	6128	6170	6210
OVERALL WIDTH	2100	2100	2100
OVERALL HEIGHT	2424	2335	2360
WHEELBASE	4035	4035	4035
CARGO AREA LENGTH (MM)	3625	3660	2860
LOAD AREA VOLUME (M2)	7	8	5.8

WEIGHTS (KG) PANEL VAN	2.2 L 120HP	2.2 L 140HP	2.2 L 180HP	BEV 110kWh
MASS IN RUNNING ORDER with driver (MIN / MAX)	2075-2150	2075-2265	2105-2285	2865-2940
GROSS VEHICLE WEIGHT (T)	3.3	3.3 – 3.5 Heavy	3.5 – 3.5 Heavy	3.5 Heavy – 4.25
MAX PAYLOAD	1225-1300	1225-1500	1290-1470	635-1460
MAX TOWING CAPACITY – BRAKED	2500	2500-3000	2500-3000	2400

STEERING (M)			
	L2	L3	L4
TYPE	Electric rack and pinion power steering		
COMPRESSION RATIO (:1)	12,5	14.3	15,3