TOYOTA GR SUPRA 2.0 SPECIFICATIONS

ENGINE	
Туре	4 in line cylinders
Valve mechanism	DOHC 16-valve with variable valve control & variable camshaft
	timing
Fuel system	Direct injection
Supercharging	Twin-scroll turbo
Displacement (cm ³)	1.998
Bore x stroke (mm)	82 x 94.6
Compression ratio (:1)	10.2 : 1
Max. power (DIN hp/ kW @ rpm)	258/190 @ 5,000-6,500
Max. torque (Nm @ rpm)	400 @ 1,550 - 4,400
Emissions level	Euro 6d Temp

TRANSMISSION	
Туре	8 speed Sports Automatic 8HP 51
Gear ratios (:1)	
1st	5,250
2nd	3,360
3rd	2,172
4th	1,720
5th	1,316
6th	1,000
7th	0,822
8th	0,640
Reverse	3,712
Final drive	3,154

PERFORMANCE	
Power to weight ratio (kg/kW - kg/DIN hp)	7.7 - 5.7
Max. speed (kp/h)	250 (electronically limited)
Acc. 0 - 100 km/h (seconds)	5,2
FUEL CONSUMPTION (I/100)	
Combined (correlated NEDC) 18-inch wheels	5.9 - 6.3
Fuel tank capacity (litres)	52
CO2 EMISSIONS (g/km)	
Combined (correlated NEDC) 18-inch wheels	135 - 143
WLTP 18-inch wheels	156 - 172

CHASSIS	
Front suspension	McPherson with double joint spring strut axle in lightweight
	aluminium-steel construction, hydraulically damped torque
	strut bearings
Rear suspension	
	Five-link axle in lightweight aluminium-steel construction
Steering	Rack & Pinion, Rack mounted Electric Power Steering
Overall ratio (:1)	15.1:1
Min. turning circle tire/body (m)	10.4/11
Brakes	
Front (diameter x thickness mm)	Ventilated disc (330 x 24) floating caliper
	Ventilated disc (348 x 36) 4 pot fixed caliper (Sport pack)
Rear (diameter x thickness mm)	Ventilated disc (330 x 20) single pot floating caliper
	Ventilated disc (345 x 24) (Sport pack)
Tyres	Michelin Pilot Super Sport
- Front	255/40 ZR18 95Y - 255/35 ZR 19 96Y
- Rear	275/40 ZR18 99Y - 275/35 ZR 19 100Y

EXTERIOR DIMENSIONS (mm)	
` '	
Overall length	4.379
Overall width	1.854
Overall height	1.299
Wheelbase	2.470
Front track	1.594
Rear track	1.589
CARGO (dm3)	
Capacity rear seats up (VDA)	290
·	
WEIGHT (kg)	
Curb weight (without driver)	1.395
Curb weight (ECE)	1.470
Gross vehicle weight (GVW)	1.710