



2024 TOYOTA PROACE CITY and VERSO Specifications

POWERTRAIN	1.5L Diesel 100HP	1.5L Diesel 130HP	1.5L Diesel 130HP	1.2L Petrol 110HP
ENGINE TYPE	4 cylinders in-line	4 cylinders in-line	4 cylinders in-line	3 cylinders in-line
DISPLACEMENT (CM³)	1499	1499	1499	1199
BORE X STROKE (MM)	75 X 84.8	75 X 84.8	75 X 84.8	75 X 90.5
COMPRESSION RATIO (:1)	16.4:1	16.4:1	16.4:1	10.5:1
MAX TORQUE (NM @ RPM)	250 @ 1750	300 @ 1750	300 @ 1750	205 @ 1750
MAX ENGINE POWER (DIN HP)	100	130	130	110
MAX ENGINE POWER (KW @ RPM)	75 @ 3750	96 @ 3750	96 @ 3750	81 @ 5500
EMISSION STANDARD	Euro 6.3	Euro 6.3	Euro 6.3	Euro 6.3
FUEL TANK CAPACITY (L)	53	53	53	53
TRANSMISSION TYPE	MT 6-SPEED	MT 6-SPEED	AT 8-SPEED	MT 6-SPEED

BATTERY ELECTRIC POWERTRAIN	BEV 50kWh
BATTERY TYPE	LITHIUM-ION
BATTERY CAPACITY (kWh)	50 kWh
BATTERY WEIGHT (Kg)	380
EV RANGE (KM)	330
MAX OUTPUT (DIN HP / KW)	136 / 100
MAX. TORQUE (NM)	270
ON-BOARD CHARGER	11 kWh
TRANSMISSION TYPE	AT

PERFORMANCE	DIESEL			PETROL	BATTERY ELECTRIC
POWERTRAIN	1.5L Diesel 100HP	1.5L Diesel 130HP 6 M/T	1.5L Diesel 130HP 8 A/T	1.2L Petrol 110HP	BEV 50kWh
MAX. SPEED (KM/H)	168	169/172	183	174	135
ACC. 0-100 KM/H (SEC)	11.5	9.8	10.6	11.0	11.2
ENERGY CONSUMPTION(L/100KM)					
COMBINED DRIVING	5.2-6.1	5.5-6.5	5.5-6.5	6.5-7.6	-
LOW SPEED	5.6-6.5	6.9-7.8	6.2-6.9	7.7-8.8	-
MEDIUM SPEED	4.8-5.8	5.3-6.2	5.3-6.2	6.1-7.2	-
HIGH SPEED	4.5-5.3	4.6-5.6	4.8-5.7	5.6-6.6	-
EXTRA HIGH SPEED	6.2-6.9	5.9-7.1	6.1-7.2	7.1-8.3	-
CO ₂ EMISSIONS (G/KM)					
COMBINED SPEEDS (g/km)	138-161	145-171	145-171	146-171	-
LOW SPEED (g/km)	145-170	180-204	164-181	174-197	-
MEDIUM SPEED (g/km)	126-151	139-162	138-163	138-162	-
HIGH SPEED (g/km)	118-140	122-146	125-150	125-149	-
EXTRA HIGH SPEED (g/km)	158-182	154-186	160-190	159-187	-

CHASSIS	
SUSPENSIONS (FRONT)	Pseudo MacPherson
SUSPENSIONS (REAR)	Deformable crossbeam
TBRAKE TYPES (FRONT / REAR)	Ventilated discs / solid disks

EXTERIOR DIMENSIONS (MM)	SHORT		LONG	
BODYTYPE	VAN	PC	VAN	PC
OVERALL LENGTH	4403	4403	4753	4753
OVERALL WIDTH (EXCL. / INCL. DOOR MIRRORS)	1848/2,107	1848/2,107	1848/2,107	1848/2,107
OVERALL HEIGHT (STANDARD / INCREASED PAYLOAD)	1880	1880	1880	1880
WHEELBASE	2785	2785	2975	2975
FRONT OVERHANG	890	890	890	890
REAR OVERHANG	726	726	886	886
GROUND CLEARANCE	145	155	160	155
FRONT TRACK WIDTH (FRONT / REAR)	1548 / 1568	1553 / 1567	1553 / 1549	1553 / 1567
APPROACH ANGLE (STANDARD / INCREASED PAYLOAD)	17.1 / 16.8	17.1 / 16.8	17.1 / 16.8	17.1 / 16.8
DEPARTURE ANGLE (STANDARD / INCREASED PAYLOAD)	21.1 / 21.4	21.1 / 21.4	21.1 / 21.4	21.1 / 21.4

LOAD AREA DIMENSIONS (MM)	SHORT		LONG	
BODYTYPE	VAN	PC	VAN	PC
MAX. FLOOR LOAD LENGTH (WITH/WITHOUT SMART CARGO)	3090 / 1817	-	3440 / 2167	-
LOAD WIDTH BETWEEN WHEEL ARCHES	1229	1195	1229	1195
MAX. LOAD WIDTH / HEIGHT	1630 / 1200	1630 / 1200	1630 / 1270	1630 / 1200
REAR DOOR OPENING WIDTH / HEIGHT	1241 / 1196	1241 / 1125	1241 / 1196	1241 / 1125
SLIDING SIDE DOOR OPENING HEIGHT / WIDTH	1072 / 675	1154 / 737	1072 / 675	1154 / 737
LOAD AREA VOLUME (M3) (WITH / WITHOUT SMART CARGO)	3.8 / 3.3	775L	4.4/3.9	1,050L

PANEL VAN

WEIGHTS (KG)	1.5L Diesel 100HP	1.5L Diesel 130HP MT	1.5L Diesel 130HP	1.2L Petrol 110HP	BEV 50kWh
PAYLOAD	650 / 1000	650 / 1000	650 / 1000	650 / 1000	800
TOTAL GROSS VEHICLE MASS	3370 / 3430	3370 / 3430	3385 / 3390 / 3400	3140 / 3220	3200 / 3205
KERB WEIGHT	1371-1670	1375-1670	1395-1697	1329-1629	1674-1918
MASS IN RUNNING ORDER	1446-1635	1450-1635	1470-1702	1404-1594	1749-1888
TOWING CAPACITY WITHOUT BREAKS	710 / 750	720 / 750	720 / 750	700 / 710 / 750	750
TOWING CAPACITY WITH BREAKS	1030 / 1050 / 1350	1030 / 1050 / 1350	970 / 1000 / 1350	850 / 880 / 1200	750

PC

WEIGHTS (KG)	1.5L Diesel 100HP	1.5L Diesel 130HP MT	1.5L Diesel 130HP	1.2L Petrol 110HP	BEV 50kWh
TOTAL GROSS VEHICLE MASS	3420	3390 / 3420	3400	3170 / 3200	3110 / 3140
KERB WEIGHT	1430-1617	1441-1657	1471-1712	1366-1563	1736-1947
MASS IN RUNNING ORDER	1505	1516-1595	1546-1650	1441-1505	1811-1881
TOWING CAPACITY WITHOUT BREAKS	750	750	750	720 / 750	750
TOWING CAPACITY WITH BREAKS	1300	1250 / 1300	1100 / 1250 / 1300	1100 / 1150	750

STEERING (M)	SHORT		LONG	
BODYTYPE	VAN	PC	VAN	PC
TYPE	Electric Power-Assisted Steering (EPAS)			
TURNING CIRCLE BETWEEN KERBS	10,82	10,79	11,43	11,49
TURNING CIRCLE BETWEEN WALLS	11,31	11,29	11,92	12,00