



2024 TOYOTA PROACE and VERSO Specifications

DIESEL POWERTRAIN	1.5L 120HP	2.0L 145HP	2.0L 180HP
ENGINE TYPE	4 cylinders in-line, turbo	4 cylinders in-line, turbo	4 cylinders in-line, turbo
DISPLACEMENT (CM³)	1499	1997	1997
BORE X STROKE (MM)	75 X 84.8	85 X 88	85 X 88
COMPRESSION RATIO (:1)	17:1	16.7:1	16.7:1
MAX TORQUE (NM @ RPM)	300 @ 1750	370 @ 2000	400 @ 2000
MAX ENGINE POWER (DIN HP)	120	144	180
MAX ENGINE POWER (KW @ RPM)	88 @ 3500	106 @ 3750	132 @ 3750
EMISSION STANDARD	Euro 6.4	Euro 6.4	Euro 6.4
FUEL TANK CAPACITY (L)	69	69	69
TRANSMISSION TYPE	MT 6-SPEED	AT 8-SPEED or MT 6-SPEED	AT 8-SPEED

BATTERY ELECTRIC POWERTRAIN	BEV 50kWh	BEV 75kWh
BATTERY TYPE	LITHIUM-ION	LITHIUM-ION
BATTERY CAPACITY (kWh)	49 kWh	75 kWh
BATTERY WEIGHT (Kg)	350	534
EV RANGE (KM)	up to 224	up to 350
MAX OUTPUT (DIN HP / KW)	136 / 100	136 / 100
MAX. TORQUE (NM)	260	260
ON-BOARD CHARGER	11 kWh	11 kWh
TRANSMISSION TYPE	AT	AT

PERFORMANCE	DIESEL			BATTERY ELECTRIC	
POWERTRAIN	1.5L 120HP	2.0L 145HP	2.0L 180HP	BEV 50kWh	BEV 75kWh
MAX. SPEED (KM/H)	160	170 - 180	170 - 185	130	130
ACC. 0-100 KM/H (SEC)	12.9 - 16	9.9 - 10.4	8.5 - 9.1	10.8 - 12.1	11.9 - 13.3
ENERGY CONSUMPTION (L/100KM)					
COMBINED	6.6 - 6.9	7.3 - 9.7	7.2 - 7.8	-	-
LOW	7.4 - 7.5	7.9 - 9.5	8.5 - 9.4	-	-
MIDDLE	5.9 - 6.3	6.8 - 7.9	6.8 - 7.5	-	-
HIGH	5.7 - 5.9	6.3 - 8.3	6.1 - 6.7	-	-
EXTRA HIGH	7.5 - 7.8	7.8 - 12.4	7.6 - 8.5	-	-
CO ₂ EMISSIONS (G/KM)					
COMBINED	172 - 180	191 - 255	189 - 205	-	-
LOW	193 - 198	207 - 250	224 - 245	-	-
MIDDLE	154 - 166	177 - 208	179 - 197	-	-
HIGH	149 - 155	165 - 218	161 - 177	-	-
EXTRA HIGH	195 - 204	205 - 326	199 - 223	-	-

CHASSIS	
SUSPENSIONS (FRONT)	Pseudo MacPherson with anti-roll bar
SUSPENSIONS (REAR)	Oblique wishbones with trailing arms
TBRAKE TYPES (FRONT / REAR)	Ventilated discs / solid discs

EXTERIOR DIMENSIONS (MM)	MEDIUM		LONG	
BODYTYPE	VAN	PC	VAN	PC
OVERALL LENGTH	4981	4981	5331	5331
OVERALL WIDTH (EXCL. / INCL. DOOR MIRRORS)	1920 / 2204	1920 / 2204	1920 / 2204	1920 / 2204
OVERALL HEIGHT (STANDARD / INCREASED PAYLOAD / ROUGH ROAD OPTION)	1895/1930/1935	1890/1925/1930	N.A./1935/1940	1890/1925/1930
WHEELBASE	3275	3275	3275	3275
FRONT OVERHANG	902	902	902	902
REAR OVERHANG	802	802	1152	1152

GROUND CLEARANCE (WITHOUT / WITH ROUGH ROAD OPTION)	150 / 175	150 / 175	150 / 175	150 / 175
FRONT TRACK WIDTH (FRONT / REAR)	1627 / 1600		1627 / 1600	
APPROACH ANGLE (STANDARD / INCREASED PAYLOAD / ROUGH ROAD OPTION)	17.1 / 16.8 / 18.1		N.A. / 16.8 / 18.2	
DEPARTURE ANGLE (STANDARD / INCREASED PAYLOAD / ROUGH ROAD OPTION)	21.1 / 21.4 / 21.4		N.A. / 15.3 / 15.2	

LOAD AREA DIMENSIONS (MM)	MEDIUM		LONG	
BODYTYPE	VAN	PC	VAN	PC
MAX. FLOOR LOAD LENGTH (WITH/WITHOUT MODULARITY)	3674 / 2512	N.A. / 2413	4026 / 2862	N.A. / 2763
LOAD WIDTH BETWEEN WHEEL ARCHES	1258	1228	1258	1228
MAX. LOAD WIDTH / HEIGHT	1636 / 1397	1618 / 1337	1636 / 1397	1618 / 1339
REAR DOOR OPENING WIDTH / HEIGHT	1282 / 1220	1212 / 1181	1282 / 1220	1212 / 1181
SLIDING SIDE DOOR OPENING HEIGHT / WIDTH	935 / 1241	1181 / 933	935 / 1241	1181 / 933
LOAD AREA VOLUME (M3) (WITH / WITHOUT MODULARITY)	5.3 / 5.8	640L	6.1 / 6.6	640L

PANEL VAN

WEIGHTS (KG)	1.5L 120HP	2.0L 145HP MT	2.0L 145HP AT	2.0L 180HP	BEV 50kWh	BEV 75kWh
PAYLOAD (MIN / MAX)	1000 - 1200	1000 - 1400	1000 - 1350	1000 - 1350	1000 - 1250	1000
GROSS VEHICLE WEIGHT (MIN-MAX)	2600 - 2800	2700 - 3100	2700 - 3100	2800 - 3100	2900 - 3100	3000
KERB WEIGHT	1656 - 1854	1511 - 2173	1760 - 2059	1774 - 2059	1845 - 2084	2020 - 2421
MASS IN RUNNING ORDER	1731	1856 - 1955	1835 - 1946	1849 - 1946	1920 - 1942	2095 - 2260
TOWING CAPACITY WITHOUT BRAKES	750	750	750	750	750	750
TOWING CAPACITY WITH BRAKES	1400 - 2000	1900 - 2500	1900 - 2200	1600 - 2200	1000	1000

PC

WEIGHTS (KG)	2.0L 145HP MT	2.0L 180HP	BEV 50kWh	BEV 75kWh
GROSS VEHICLE WEIGHT (MIN-MAX)	2700 - 3100	2757 - 3100	2771 - 3030	2946 - 3130
KERB WEIGHT	1982 - 2189	1911 - 2176	1943 - 2198	2136 - 2486
MASS IN RUNNING ORDER	2057 - 2092	1986 - 2115	2018	2211 - 2406
TOWING CAPACITY WITHOUT BRAKES	750	750	750	750
TOWING CAPACITY WITH BRAKES	1800	1900	1000	1000

STEERING (M)	MEDIUM		LONG	
BODYTYPE	VAN	PC	VAN	PC
TYPE	Electric Power Steering			
TURNING CIRCLE BETWEEN KERBS	12.4			
TURNING CIRCLE BETWEEN WALLS	12.9			
TURNING RADIUS	6.2			